

5F Annex Dragon Pearl Plaza  
2123 Pudong Avenue  
Shanghai 200135 - P.R. CHINA  
Tél. : +86 21 68 55 50 32  
Fax : +86 21 68 55 50 33  
E-mail : [ctcshanghai@ctcgroupe.com](mailto:ctcshanghai@ctcgroupe.com)

Report No.: S190201402\_1

25 February 2019

朱天宇 / 15726930231@163.com

**APPLICANT:** ZHEJIANG MENGTAI SPECIAL MATERIALS  
TECHNOLOGY CO., LTD 浙江蒙泰特种材料科技  
有限公司 (C39251)  
浙江嘉兴桐乡梧桐经济开发区齐鸣路270号  
. ZHEJIANG  
CHINA

Date of receipt : 21 Feb. 2019  
Testing period : 21 Feb. 2019  
: 22 Feb. 2019

**Buyer:** ---

**Sample description:** 白色

Test(s) requested : ---  
Service : REGULAR  
Brand / Section : ---  
Season : ---  
End use : ---  
Factory name : ---  
Factory code : ---


**For CE Marking : Yes**  
Previous report : ---  
Product category : ---  
Product type : ---  
Test stage : FIRST TEST  
Supplier name : ---  
Exported to : ---

**1. Conclusion:**

	Tests description	Conformity
	<b>EN 388</b>	
1	Abrasion resistance : 2016	<b>Level 2</b>

Pass: requirements met    Fail: requirements not met    None: no requirement for this test    N/A: not applicable

Approved by



Henry YAN  
Laboratory Manager

Report No.: S190201402\_1

25 February 2019

APPLICANT: ZHEJIANG MENGTAI SPECIAL MATERIALS  
TECHNOLOGY CO., LTD 浙江蒙泰特种材料科技  
有限公司 (C39251)

**2. Sample(s) description assigned by laboratory:**

<u>Size</u>	<u>Analyzed product</u>	<u>Description</u>	<u>Sample information</u>
	MATERIAL	Material	



190201402

Report No.: S190201402\_1

25 February 2019

APPLICANT: ZHEJIANG MENGTAI SPECIAL MATERIALS  
TECHNOLOGY CO., LTD 浙江蒙泰特种材料科技  
有限公司 (C39251)

### 3. MATERIAL/

#### Material

	Method	Client Requirement	Unit	Result	Conformity
(+) <b>4.1. Abrasion resistance : 2016</b>	EN 388 : 2016				
Deviation from the test method				No	
used consumables - abrasive				Klingspor PL31B Grit 180	
used consumables - adhesive				3M Scotch	
Number of cycles at the hole detection				1200	
Number of cycles at the hole detection (2)				1900	
Number of cycles at the hole detection (3)				7800	
Number of cycles at the hole detection (4)				1000	
Performance level				2	

### END OF TEST REPORT

(+)CNAS accreditation

Table of Performance Level for Glove

Test Item	Performance Level					
	0 <sup>##</sup>	1	2	3	4	5
<b>Abrasion Resistance (EN 388)</b> Number of cycles (minimum)	<100	100	500	2000	8000	---

## Performance level 0 means the glove falls below the minimum performance level for the given individual hazard